

EL5100 KVM Extender

DVI and USB 2.0



The **EL5100 KVM Extender**, powered by **ExtremeLink™** technology, lets you place a computer up to 330 ft (100 m) away from the workstation area, connected with a single inexpensive Cat 5 (or better) cable. The system supports full HD video and USB 2.0, including control of the keyboard, mouse, webcam, flash drive, speakers, microphone and other USB 1.1 and USB 2.0 devices.

Applications include security, medical, interactive digital signage and industrial environments where the computer must be remotely accessible.

Key Product Features

- **Remote Desktop:** Increases IT security while improving PC provisioning and maintenance.
- **Full HD Video:** Uncompressed 1920 x 1200 resolution, 24-bit color depth.
- **Long Distance:** 330ft(100m) over single solid core Cat 5 cable.
- **Audio:** Supports USB audio devices.
- **USB 2.0 Support:** USB 2.0 supporting all device types. Recommended with keyboard, mouse, flash drive, printer, microphone, USB 1.1 web camera and other USB devices which require moderate amounts of bandwidth.
- **OS Support:** Compatible with all major operating systems. No drivers required.
- **Installation Ease:** True plug and play (no set up required). Utilizes a single Cat 5 (or better) cable for desktop extension simplifying installation.
- **Rack Mountable:** Allow for up to two units to be mounted in a 19"/1U rack mount kit.



Specifications subject to change without notification.
©2011 Icron Technologies Corp.
#90-00909-A01

scanmagnetics.com

EL5100 Specifications



Specifications subject to change without notification.
©2011
Icron Technologies Corp.

VIDEO PERFORMANCE

| | |
|------------------------|---|
| Video: | 1920 x 1200 at 24-bit color depth |
| Video Latency: | Less than 1ms |
| Reach: | 330 ft (100m) at full resolution |
| Interconnection Cable: | RJ45 connector supporting solid core Cat 5 (or better) cable. Solid core Cat 6 is recommended for best results. |

LOCAL EXTENDER

| | |
|-------------|---|
| Video: | DVI-D Video Input (24-pin connector), HDMI (with adapter) |
| USB: | 1 x USB Type B |
| Dimensions: | 4.4" x 6.9" x 1.18" (112mm x 175mm x 30mm) |
| Power: | 5V DC, 3A DC (15W) |

REMOTE EXTENDER

| | |
|--------------|--|
| Video/Audio: | DVI-D Video Output (24-pin connector), HDMI (with adapter) |
| USB: | 3 x USB Type A |
| Dimensions: | 4.4" x 6.9" x 1.18" (112mm x 175mm x 30mm) |
| Power: | 5V DC, 3A DC (15W) |

ENVIRONMENTAL

| | |
|------------------------|-------------------------------|
| Operating Temperature: | 32°F to 104°F (0°C to 40°C) |
| Storage Temperature: | -4°F to 158°F (-20°C to 70°C) |
| Operating Humidity: | +20% ~ 80% (non condensing) |
| Storage Humidity: | +10% ~ 90% (non condensing) |

CERTIFICATIONS

| | |
|-------------|--|
| EMC: | FCC Class A, CE, ICES-003 |
| Compliance: | RoHS |
| HDCP: | Not supported. Support can be added in specific use cases. |

Ordering Information

| PART NUMBER | NAME | DESCRIPTION |
|-------------|------------------------|---|
| i308 | EL5100-EU | EL5100 systems include a Local Extender, a Remote Extender, a USB cable, a DVI cable and two International power adapters with country specific power cord. |
| i287 | Rack Mount Adapter Kit | Four Brackets and Stencil (Screws not included). |

scanmagnetics.com